

BluOcean™ USB GSM Modem

BluOcean™ popular range of World-class standard GSM and GPRS modems are widely used by corporations and software houses across the world. To ensure quality and speed maximization, only top quality chipset from France WAVECOM WISMO™ (World No 1 Provider of Integrated Wireless Modules) is used in the BluOcean™ modems.



Technical Specification

- SIM card holder integrated
- 3V SIM Interface
- Activity Status LED Indication
- Power Output: Class4 (2W @ EGSM 900/GSM 850)
Class1 (1W @ GSM 1800/1900)
- Normal operation temperature: -20 to 55°C
- Operating Voltage : 5 to 24VDC
- Typical idle mode supply current: 5mA
- Baud rates: 300-9600 bits/s
- Compliant with ETSI GSM Phase 2 +
- Control via AT commands (GSM07.07 & 07.05)

Design

- USB Interface
- Silvery Grey Color With Metal Casing
- Weight 100g With Dimension 98x54x25mm

SMS Specification

- Text and PDU mode
- Cell broadcast
- Point to Point MO and MT

Fax Specification

- Group 3 (Class 1,2)

Supported Operating System

- Windows 2000, NT, XP, Vista

Included Accessories



Type	Frequency	Coverage	Model
Dual Band	GSM 900/1800 MHz	Asia & Europe	GSM-U-A1
Dual Band	GSM 850/1900 MHz	USA & Canada	GSM-U-U1
Quad Band	GSM 850/900/1800/1900 MHz	Worldwide	GSM-U-W1

World No 1 Integrated Wireless Modules Embedded - Wavecom WISMO™

Directly connect to computer. Easily plug and play. Ideal for all users!